

848 – ANTI-GRAFFITI COATING

SECTION 848

ANTI-GRAFFITI COATING

848.1 DESCRIPTION

Prepare and apply the anti-graffiti coating to the surfaces to be protected, as designated in the Contract Documents.

BID ITEM

Anti-Graffiti Coating

UNITS

Square Yard

Note: If this bid item is not included in the Contract Documents, this work is subsidiary to other items in the contract.

848.2 MATERIAL REQUIREMENTS

Provide anti-graffiti coating that complies with **DIVISION 1700**.

848.3 CONSTRUCTION REQUIREMENTS

Provide copies of the manufacturer's material safety and technical data sheets. The technical data must include detailed application instructions, minimum and maximum application temperatures and recommended time between coats.

Prepare the surfaces that will receive the anti-graffiti coating in accordance with the manufacturer's recommendations before applying the coating.

Store, mix, apply and cure the anti-graffiti coating as recommended by the manufacturer.

848.4 MEASUREMENT AND PAYMENT

When shown as a bid item in the contract, the Engineer will measure the anti-graffiti coating by the square yard. If the anti-graffiti work is shown in the Contract Documents, but the bid item for this work is not included in the Contract Documents, the Engineer will not measure the anti-graffiti coating for separate payment.

Payment for "Anti-Graffiti Coating" at the contract unit price is full compensation for the specified work.